

# Coding Table: "VISTA-Oil-round" level gauge

	VL	A	15	ST	G	3	150	M	0
<b>Type</b> VL = "Vista-Oil-round" Level gauge	[Diagram: VL - vertical line]								
<b>Style</b> A = Vertical C = Horizontal Lock Nut D = Horizontal Banjo Bolt E = Horizontal Banjo Bolt with Port	[Diagram: A - vertical line, C - horizontal line, D - horizontal line, E - horizontal line]								
<b>Sight Pipe diameter (mm)</b> 15 mm = standard 18 mm	[Diagram: 15 - vertical line, 18 - vertical line]								
<b>Material metal parts</b> ST = Steel zink plated SS = AISI 316L stainless steel (DIN 1.4404)	[Diagram: ST - vertical line, SS - vertical line]								
<b>Mounting thread standard</b> G = BSW parallel (DIN 259) R = BSPT tapered (EN10226) N = NPT (US-Norm ANSI) ① M = Metrisch (s. note)	[Diagram: G - vertical line, R - vertical line, N - vertical line, M - vertical line]								
<b>Mounting thread size</b> 0 = without / Banjo screw only (style D) 1 = 1/4" 2 = 3/8" 3 = 1/2" 4 = 3/4" ① M = Metrisch	[Diagram: 0 - vertical line, 1 - vertical line, 2 - vertical line, 3 - vertical line, 4 - vertical line]								
<b>Sight Pipe length (mm)</b>	[Diagram: 150 - vertical line]								
<b>Level marks (mm)</b> ① 0 = without level marks M = with level marks Marks to be specified by order	[Diagram: 0 - vertical line, M - vertical line]								
<b>① Optional Accessories (available for Model E only)</b> 0 = Drain Screw 1 = Thermometer 2 = Sampling Port 3 = Sampling Port with a Pitot Tube 4 = Drain Valve	[Diagram: 0 - vertical line, 1 - vertical line, 2 - vertical line, 3 - vertical line, 4 - vertical line]								

① Because of the variety of options these details are cleared with the receipt of your order. Technical details are provided within the relevant contract documents.